

Trademarks and disclaimers

IEEE believes the information in this publication is accurate as of its publication date; such information is subject to change without notice. IEEE is not responsible for any inadvertent errors.

Other tradenames and trademarks in this document are those of their respective owners.

The Institute of Electrical and Electronics Engineering, Inc. 3 Park Avenue, New York, NY, 10016-5997, USA

Copyright © 2000 by the Institute of Electrical and Electronics Engineers, Inc. All rights reserved. Published December 2000. Printed in the United States of America.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

To order IEEE Press publications, call 1-800-678-IEEE.

Print: ISBN 0-7381-2601-2

SP1122

See other standards and standards-related product listings at: http://standards.ieee.org/

The publisher believes that the information and guidance given in this work serve as an enhancement to users, all parties must rely upon their own skill and judgement when making use of it. The publisher does not assume any liability to anyone for any loss or damage caused by any error or omission in the work, whether such error or omission is the result of negligence or any other cause. Any and all such liability is disclaimed.

This work is published with the understanding that the IEEE is supplying information through this publication, not attempting to render engineering or other professional services. If such services are required, the assistance of an appropriate professional should be sought. The IEEE is not responsible for the statements and opinions advanced in this publication.

Library of Congress Cataloging-in-Publication Data

IEEE 100: the authoritative dictionary of IEEE standards terms.--7th ed.

p. cm. ISBN 0-7381-2601-2 (paperback : alk. paper)

Electric engineering—Dictionaries.
Electronics—Dictionaries.
Electronics—Dictionaries.
Electric engineering—Acronyms.
Electronics—Acronyms.
Computer engineering—Acronyms.
Institute of Electrical and Electronics Engineers.

TK9 .I28 2000

621.3'03--dc21

00-050601

Content

Introduction

How to Use

Categories

Trademark:

The Author

Abstracts a

Non-IEEE S

The Authoritative

which contains manually or meare to be subsequently punched de generator.

containing information that is to machine-readable document. example, an original invoice, a (C) 610.10-1994w (C) 610.2-1987

ut electrical power. The ratio of emitted optical supplies a piece of trace infor-(C/PA) 1224.1-1993w

o of a source, usually the signal or a source specification nission system) Potential refer-(Std100) 812-1984w (E) [43

ds of a device, or network. See pedance presented by a source of (C/PA) 1387.2-1995

on line and the status (i.e., opened rk analysis; input impedance. (SP/IM/HFIM) 151-1965w, [40] s defined to begin at the power smission line. In network appliassociated with the transmission vary depending on the location impedance of an electrical sys-(PE/PSR) C37.113-1999

st applications to test the UUT rce impedance. Different LISNs es with each input line to provide mnects used in the system should mpedance stabilization networks is included in the source impedat the power source return ter-

on process is represented. For exualysis) A node having only outpedance. (COM/TA) 661-1979r od to be 900 Ω resistive. See also. mess ratings of telephone conwrite a computer program. Con-The language in which the input impedance used for determining (C) 610.2-1987, 610.12-1990 (CAS) 155-1960w (PEL) 1515-2000

t on the protected line. Note that ninal that contributes a significant originates data. See also: desti (C/BA) 1355-1995

Morse code, a duration of two unit intervals between char-

tions of an element (bit); an open line in a neutral circuit. In

;-zag winding. s within the duration of fault clearcontribute significant amounts of t current. For instance, large synation to be connected to a terminal ortion of a source specification ded neutral connected to the line ed faults involving ground if they be a significat source of zero-se-(PE/PSR) C37.113-1999 (C/PA) 1387.2-199:

> source, radioactivity standard See: radioactivity standard source, radioactive See: radioactive source.

source resistance rating The value of source resistance that, source resistance The resistance presented to the input of a device by the source. See also: measurement system source. band by one-half its width. See also: measurement system. resistance, will either double the dead band or shift the dead when injected in an external circuit having essentially zero (EBC/EMI) [112] (EBC/EMI) (112)

source role Where the software exists in a form suitable for provides a repository where software may be stored and proremoved by a task initiated by the manager. The source role pository of software from which the manager may choose to distribution, forming a context for the establishment of a revides access for those roles that require the software distribute to targets. Software exists in the source until it is (C/PA) 1387.2-1995

source routing (I) A bridging technique where frames contain (3) The capability for a source to specify the path that a frame must know the route to the destination before sending the the list of bridges and networks that must be traversed for the will use to traverse the bridged network Within the source routed frame, the station specifies the route that the frame will traverse. (C/LM) 8802-5-1998 (2) A mechanism to route frames through a bridged LAN. frame. Contrast: spanning tree. frame to reach the destination. In this scheme, the transmitter (C/LM/CC) 8802-2-1998 (C) 610.7-1995

Source Routing Transparent (SRT) The bridging technology source segment In a hierarchical database, a segment that contains the data used to construct a secondary index. specify the path through the bridged network (source routing the transparent bridging rules allowing the source station to defined by ISO/IEC 10038:1993, annex C, as an extension to (C/LM/CC) 8802-2-1998 (C) 610.5-1990w

source-to-line impedance ratio (SIR) The ratio of the source source statements (SS) The encoded logic of the software prod ource/sink device Source devices originate signals, whereas vices include channel banks and digital crossconnect systems sink devices terminate signals. Examples of source/sink de-(COM/TA) 1007-199h (C/SE) 1045-1992

space (1) (data transmission) One of the two possible condi-SPA See: scratchpad area. SP See: space character. impedance behind a relay terminal to the line impedance (PE/PSR) C37.113-1999

tended for the storage of data such as a location in a storage or more space characters. as the size of a single character. (D) (data management) One medium. (C) (data management) A basic unit of area such to a prescribed format. (B) (data management) A site in-(2) (A) To advance the reading or display position according acters and six unit intervals between words. (PE) 599-1985w

(3) The absence of a signal; for example, in data communications, the "zero's" state. Contrast: mark. (C) [20], 610.5-1990 (C) 610.10-1994v

QSD 399-1990

(#2,204) 83-1973w be inpartition to the base tan of w) to the reference power of r pewert, 10⁻¹⁰ W. an account of wares (for ease) The start of a delay act; that is, the peal. For act opposite of conserver, the the AD the explica a post of the (the hard portion of a source oper Political. not repeate in the language used by the as present yet not on a madeure. al Adocument continuing safety and company. For exemple, an original year card, or a machine-resolute car Countries soran total mice of a scene, would the M veriging (20) contracting on the requirement Agrandings and on the requirement of the requirement of the region of the response of the respons Many weeks Chillishee date 900 Dataset A. Sel-J super quant is amosting, a parted for extending the justice in which a device desiral the congration and impacts has the parter trap researching for this for quantity. swere resistance saided. The value of source reconver-vieta labored in an eventual course bring essentially resistance, will assume adopted for each band at \$40 kins band by executed his width. See after memorated print asera programa (sathweek) A seesy Are program doo more ke complete, connobine, are elementar operature for order to be command by a complete. Connectic about program. (C) 638.12.1990 GI (A) To advance to reading or exp the temporary bridging rates allowing the specify the path-through the bedged convent area resistance. The positioners occurrenced by the legal of a device by the source. See also recovered by take. CATTON THOMPSON OF A SUMMER FOR EXCENSION. I CONTRACT THOMPSON ON COMPOSIT STATE. trins the data rend to contract a recoupled AT the capability for a student in upon the capability for a student in the capability for a s to the way the property of the entim, redirectely standard Ser refereively station Handiag lappedance make (SSR) The state of the sor edition behind a miny removed in the line impediance (FSB/SR) CTI.115-1 measure (SS) The encoded legal o